

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition	Error
1	IS&R	L1	4396	((385/16-18) or (359/223-226)).CCLS.	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:48			0
2	BRS	L2	2493	(mems or microelectromechanical) with (switch or switches or mirror or mirrors or micromirror or micromirrors or reflector or reflectors or deflector or deflectors)	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:50			0
3	BRS	L3	927	(1 and 2) or 2.ti,ab.	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:50			0
4	BRS	L4	3608	(serpentine or corrugated) with (hinge or hinges or pivot or pivots or spring or springs or flexure or flexures)	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:52			0
5	BRS	L5	42	3 and 4	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:52			0
6	BRS	L7	129	4 same (damping or damped or damper or viscous or viscoelastic)	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:53			0
7	BRS	L8	140	6 or 7	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 14:53			0
8	BRS	L6	11	5 and (damping or damped or damper or viscous or viscoelastic)	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 15:23			0
9	BRS	L9	0	5 and ((variable or varying or varied) near3 spring near3 (constant or constants))	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 15:23			0

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition	Errors
10	BRS	L10	3	4 same ((variable or varying or varied) near3 spring near3 (constant or constants))	USPAT; US-PGPUB ; EPO; JPO	2004/ 01/03 15:23			0